

# SX-4025

CRYSTAL

SMD



TYPICAL APPLICATIONS

Bluetooth, Wireless LAN, Audio Equipment, MP3, PDA, Cellular

FEATURES

Ultra-thin, Ceramic SMD Package, Seam Sealed, Lead-free Design, Tight Tolerance and Stability, Reflow Soldering, Emboss Taping, RoHS Compliant Standard

DIMENSIONS

4.0x2.5x0.7[mm]



TYPICAL SPECIFICATIONS

Model	SX-4025	
Nominal Frequency Range	12.000~50.000MHz	
Standard Frequency	13.000, 16.000, 26.000, 32.000MHz	
Vibration Mode	Fundamental [AT]	
Frequency Tolerance (@ +25°C)	±10 ppm	
Freq. Temp. Characteristics (Ref. to 25°C)	±10 ppm	±15 ppm
Operating Temperature Range	-10°C~+60°C	-30°C~+85°C
Storage Temperature Range	-40°C~+90°C	
Load Capacitance	Series, 10pF, 12pF, 16pF	
Shunt Capacitance	5pF Max.	
Drive Level	10μW (100μW Max.)	
Equivalent Series Resistance	See Table 1	
Aging (+25°C)	±1, ±3 ppm / year Max.	

Please consult with our sales department for other parameters.

\*Package quantity 1,000 pcs max./reel.

OUTLINE DIMENSIONS  
Unit:mm




TABLE 1: ESR

AT-cut Fundamental	
Frequency (MHz)	ESR (Ω)
12.000 ~ 12.999	100
13.000 ~ 18.999	80
19.000 ~ 39.999	60
40.000 ~ 50.000	50

All specifications are subject to change without notice.